

maintained. Where occasional work tasks require more light than that which is consistently and permanently provided, supplemental lighting shall be used.

(b) The lighting intensity shall be measured at the task/working surface, in the plane in which the task/working surface is present.

(c) Lights shall, so far as possible, be placed so that they will not shine in the eyes of employees.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.124 Dockboards (car and bridge plates).

(a) *General.* The employer shall provide safe means of passage between different surface levels and across openings.

(b) [Reserved]

(c) *Dockboards (car and bridge plates).*

(1) Dockboards shall be strong enough to support the loads imposed on them.

(2) Portable dockboards shall be anchored in position or be equipped with devices to prevent their movement.

(3) Hand holds or other effective means shall be provided on portable dockboards to permit safe handling.

(4) Positive means shall be used to prevent railcars or highway vehicles from being moved while dockboards or bridge plates are in position.

(5) Be designed, constructed, and maintained to prevent vehicles from running off the edge.¹⁰

(6) Dockboards shall be well maintained.

(d) *Ramps.* (1) Ramps shall be strong enough to support the loads imposed on them and be designed, constructed, and maintained to prevent vehicles from running off the edge.¹¹

(2) Ramps shall be equipped with a guardrail meeting the requirement of § 1917.112(c)(1) if the slope is more than 20 degrees to the horizontal or if em-

ployees could fall more than 4 feet (1.22 m).

(3) Ramps shall have slip-resistant surfaces.

(4) When necessary to prevent displacement by vehicle wheels, steel plates or similar devices used to temporarily bridge or cover uneven surfaces or tracks, shall be anchored.

(5) Ramps shall be well maintained.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997; 65 FR 40942, June 30, 2000]

§ 1917.125 Guarding temporary hazards.

Ditches, pits, excavations and surfaces in poor repair shall be guarded by readily visible barricades, rails or other equally effective means.

§ 1917.126 River banks.

(a) This section applies to temporary installations or temporary operations near a river bank.

(b) Where working surfaces at river banks slope so steeply that an employee could slip or fall into the water, the outer perimeter of the working surface shall be protected by posting or other portable protection such as roping off. In these situations, employees must wear a personal flotation device meeting the requirements of § 1917.95(b).

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.127 Sanitation.

(a) *Washing and toilet facilities.* (1) The employer shall provide accessible washing and toilet facilities sufficient for the sanitary requirements of employees. The facilities shall have:

(i) Running water, including hot and cold or tepid water at a minimum of one accessible location (when cargo handling is conducted at locations without permanent facilities, potable water may be provided in lieu of running water);

(ii) Soap;

(iii) Individual hand towels, clean individual sections of continuous towel-eling or warm air blowers; and

(iv) Fixed or portable toilets in separate compartments with latch-

¹⁰When the gap to be bridged to greater than 36 inches (.91 m), an acceptable means of preventing vehicles from running off the edge is a minimum side board height of two and three-quarter inches.

¹¹When the gap to be bridged is greater than 36 inches (.91 m), an acceptable means of preventing vehicles from running off the edge is a minimum side board height of two and three-quarter inches.